












	standards	characteristics or properties	declared values
	ISO 10545-3	assorbimento d'acqua water absorption	<0.5%
	ISO 10545-4	resistenza alla flessione breaking strength	35 N/mm <sup>2</sup>
	ISO 10545-13	resistenza agli acidi resistance to acid	GLA
	ISO 10545-12	resistenza al gelo frost resistance	resiste frost proof
	ISO 10545-14	resistenza alle macchie stain resistance	4
	ISO 10545-2	planarità surface flatness	±0.5%
	ISO 10545-2	spessore thickness	10 mm
	DIN51097 DIN51130 DCOF BOT 3000	coefficiente d'attrito (scivolosità) static coefficient of friction	A R10 > 0.42
	DIN51097 DIN51130 DCOF BOT 3000	coefficiente d'attrito (scivolosità) static coefficient of friction	A+B+C R11 > 0.42
		variazioni cromatiche color shade variations	V3 variazione moderata V3 moderate variation
	ISO 10545-2	ortogonalità orthogonality	±0.6%

IMBALLI - PACKING

mm	inch		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kg/pl kgs/pal
60x120	24"x48"	2thick_20mm rettificato	20	1	0.72	32.25	30	21.60	967.50
60x120	24"x48"	rettificato	10	2	1.44	31.80	30	43.20	954.00
60x60	24"x24"	rettificato   grip	10	3	1.08	24.13	40	43.20	956.20
30x60	12"x24"	rettificato	10	6	1.08	24.09	40	43.20	963.60
80x80	32"x32"	rettificato	10	2	1.28	27.37	40	51.20	1094.80
12x53	423/32"x21"	chevron	10	12	0.76	17.70	48	36.48	849.60
7.4x30	3"x12"	rettificato	10	40	0.89	19.50	60	53.28	1170.00
30x30	12"x12"	mosaico		11	0.99	20.00	36	35.64	720.00
30x60	12"x24"	plank		5		19.65			
25x34	10"x13"	hexagon		6		11.10			
7x60	23/4"x24"	battiscopa smaltato rettificato		12		11.16			
9.5x80	4"x32"	battiscopa smaltato rettificato		8		14.24			
30x60	12"x24"	gradino rettificato   grip		8		31.60			
30x60x4	12"x24"x1 1/3"	gradone costa retta rettificato   grip		4		19.40			
60x120x4	24"x48"x1 1/3"	gradone costa retta rettificato		2		34.80			
30x30x4	12"x12"x1 1/3"	gradone angolare costa retta   grip		2		4.40			
60x120x4	24"x48"x1 1/3"	gradone angolare costa retta		1		18.20			
30x60x5	12"x24"x 2"	elemento a L   grip		4		17.20			

FUGHE - JOINT - JOINT - FUGE

per materiale **rettificato** prevedere una fuga di almeno 2 mm sul monoformato e necessariamente 3 mm sul multiformato

for **rectified** material, we recommend a minimum of 2 mm of grout when using one size of piece only and 3 mm for multi-size laying solutions

pour le matériel **rectifié** prévoir un minimum de 2mm de joint et 3mm pour la pose multiformat

fuer **rettifiziertes** material-monoverlegung wollen sie bitte eine fuger von 2 mm vorsehen – fuer modulerlegung eine fuger von 3 mm